


Shaft bearing

rubber, for french sailing boats.



Article	Ø A mm.	Ø B mm.	C mm.
2727700	22	29	75
2727701	22	36	80
2727702	25	36	100
2727703	25	40	120
2727704	30	40	120
2727705	35	54	140
2727706	40	54	140

**Gland packing**

Greased square braided hemp for propeller shaft assembly sealing. Package 2 m.



Article	Dims. mm.	Ø Shaft mm.
2727806	6 x 6	20 / 25
2727808	8 x 8	25 / 35
2727810	10 x 10	40 / 60

Rope cutter

stainless steel AISI 316. Nylon rope, stainless steel cables (Ø mm. 4 - 6), net cutter.



Article	Ø Shaft mm.	Ø External mm.	Thickness mm.
2732825	25	80	17
2732826	30		
2732827	35	100	
2732828	40		
2732829	45	120	
2732830	50		

Clump rope cutter

(two pieces) in stainless steel AISI 316. rNylon rope, stainless steel cables (Ø mm. 4 - 6), net cutter. It is installed or uninstalled without take the propeller off.



Article	Ø Shaft mm.	Ø External mm.	Thickness mm.
2732925	25	80	22
2732926	30		
2732927	35	100	
2732928	40		
2732929	45	120	
2732930	50		

Tube

in fiberglass (GRP) for shaft



Article	Ø shaft mm.	Ø In. mm.	Ø Out. mm.	L mm.
2728725	25	35	43	1200
2728730	30	40	49	
2728735	35	47	55	
2728740	40	52	60	
2728745	45	56	65	
2728750	50	60	70	

